

**Model: RMM-7X2T**  
**3U, Dual 7" TFT LCD Rack Mount Monitor, with Touch Screen**



Specification	
Product Model	RMM-7X2T
LCD Panel	Display Type : 7" VGA TFT LCD Resolution : 800×480 Max. color : 262K Luminance : 350 cd/m2 View Angel ( L/R ,U/D ) : 50/50, 50/50 Pixel Pitch : 0.1905 x 0.1905 mm Contrast Ratio : 200 : 1 Response Time : 30 ms Power Consumption : 4W LCD MTBF : 50,000hrs
Signal Input	VGA , Video, S-Video
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Touch Screen	Internal USB or RS-232 interface controller Type: Analog resistive type : 25VDC ≥ 20MΩ Resolution: continuous Light transmission: 80% or more Power consumption:<5V @1mA Surface hardness : 3H Operating force : ≤100g Life expectancy : 35 Million Operation system : Window 2000 / XP / Vista / 7 / CE, DOS , Linux
Power Supply	DC12V@ 4A /48W ,external ac adapter
Construction	Heavy duty steel
Environment	Operating temperature: 32 °F~113 °F (0 °C to 45 °C) Storage temperature: -4 °F~140 °F (-20 °C to 60 °C) Storage humidity: 10% to 95%@ 40°C , on-condensing Vibration: 10 ~ 150Hz, 0.15mm 10 cycles 1G Shock: 30G peak acceleration (11 msec. duration)
Safety	CE/FCC/Rohs

Dimension W x H x D ( mm )	Dimensions: 482.6*133* 62.7mm Packing Dimension: 600x190x 320mm
Weight	NET weight: 5.7KG Gross weight: 6.7KG

## Structure Diagram Unit :mm

