

Model: SSPM-22APCT-UHB
21.5" Ultra High Brightness Industrial Stainless Steel Panel Monitor with PCT Touch



Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 21.5" Full HD LED panel support 1920 x 1080 pixels
- Front 5.5mm Stainless Steel bezel with NEMA4 / IP 65 compliance
- Front flat glass (6H Hardness) with projected capacitive Multi Touch Screen
- Supports 10 points multi-touch via USB interface in Windows 7/8.1/10...
- Slim design for Panel mount / Wall mount easy installation
- Input signal : VGA + DVI-D + HDMI + Audio + USB
- Meet standard VESA hole (75x75 & 100X100mm), support desktop stand/wall mount /swing arm mounting

Application:

Kiosk; Digital Signage; Factory Automation; Processor Automation; Marine / Offshore Industrial ...

Specification	
Product Model	SSPM-22APCT-UHB
LCD Panel	Display Type : 21.5" Full HD <u>LED Panel</u> Resolution : 1920x1080 Max. color : 16.7M Luminance : 1,500 cd/m2 View Angel : 170°(H), 160°(V) Contrast Ratio : 1000 : 1

	LED backlight lifecycle : 50,000hrs
Signal Input	VGA + DVI-D + HDMI + Audio + USB
OSD	Auto; Menu; Left; Right; Exit/Select; Power On/Off
Touch Screen	Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness : 6H Operation system : DOS; Windows XP / 7 / 8.1 / 10; Linux
Power Supply	Input: 100~240VAC, 50/60Hz Output: DC12V@ 5A /60W, external AC power adapter
Construction	Stainless Steel front panel with heavy-duty steel chassis
Environment	Operating temperature: 0 °C to 60 °C Storage temperature: -20 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: 50 to 500HZ 1G PTP Shock: 10G /peak(11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	585 x 360 x 50 mm

Ordering Information

SSPM-22APCT-UHB	21.5" Ultra High Brightness Industrial Stainless Steel Panel Monitor with PCT Touch
-----------------	---

Structure Diagram (Mounting Hole Size: 556 x 347 mm)

