

Model: STM-19
19" CCTV Security Monitor



Main Feature

- 19" SXGA TFT LCD Panel support 1280 × 1024 pixels
- Heavy duty steel chassis
- Rugged construction design
- Input signal : VGA + HDMI + 3 x BNC + Audio
- Build in 2 x 2 Watts stereo speaker
- OSD control keys to optimize the display, with Infrared Remote Controller
- AC 100-240V wide range AC power input
- Meet standard VESA hole (75 x 75 mm), support desktop stand/wall mount /swing arm mounting

Specification	
Model	STM-19
LCD Panel	Display Type: 19" SXGA TFT LCD Resolution: 1280 x 1024 Max. color : 16.7M Luminance : 450 nit View Angel : 178°(H), 178°(V) Pixel Pitch : 0.294 x 0.294 mm Contrast Ratio : 1000 : 1 Response Time : 8 ms Power Consumption : 24W LCD MTBF : 50,000hrs
Video System	PAL, NTSC 640 x 480p @ 60Hz 720 x 480p @60Hz 720 x 576p @ 50Hz

	1,280 x 720p @ 50/60Hz 1,920 x 1,080i @ 50/60Hz 1,920 x 1,080p @ 50/60Hz
Filter Type	3D Combo filter
Signal Input	VGA + HDMI + 2 x BNC + YPbPr (BNC) + 2 x Audio
Signal Output	BNC loop-out (for video recording)
Speaker	Built-in 2 x stereo speakers (2 watt)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall
Power Supply	Input: 100~240VAC, 50/60Hz
Power Consumption	Maximum: 35 watt
Construction	Heavy duty steel chassis
Environment	Operating temperature: 0 °C to 50 °C humidity: 10% to 95%, non-condensing
Dimension W x H x D (mm)	397 x 325 x 70
Net Weight	7 KG
Ordering Information	
STM-19	19" CCTV Security Monitor

Structure Diagram (unit: mm)

