

Model: KVM-1701COMBO-S
1U Rackmount 17" TFT LCD ,with 1 port KVM switch (Short Depth)



Main Feature

- 1 PS/2 console controls 1/8/16 directly connected computers
- 86 keys keyboard with touch pad
- Cascade switches up to 8 levels and Mix switches between Cat5 & DB-15 KVM
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch/PCs
- Superior video quality - Up To 1024X768, DDC2B
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- Firmware upgradeable for staying compatible with new coming computers
- Metal case, rack mountable Support DDC2B for all ports

Specification		
Product Model	KVM-1701COMBO-S	
LCD	Size	17" TFT
	Resolution	1280 x 1024
	Max.color	16.7 M
	Luminance	300 cd/m2
	View Angle	178° (H) , 178° (V)
	Pixel Pitch	0.264 x 0.264 (mm)
	Contrast Ratio	1000 : 1
LEDs / Port	1	
Power	1	
Computer Connections	1	
Maximum Computer Connections	225	
Computer Connectors	2 x PS2, 1 x USB, 1 x VGA	

Daisy Chaining	Daisy Chainable up to 8 levels ; Connector : DB-15 (female type)	
Computer Selection	On Screen Display (OSD) , Hot Key , Push Button	
Hotkey	Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)	
Auto-Scan Intervals	5 ~ 99 Sec.	
Keyboard / mouse Emulation	PS/2	
Power Adapter	AC 100-240V , 50/60Hz , DC 12V / 4A , 48Watt	
Housing	Metal	
Size	19" Rack mount, 1U	
Environment	Operating Temperature	0 - 50 °C
	Store Temperature	-20 -60 °C
	Humidity	10% to 90%,non-condensing
Physical Dimensions (W x H x D)	482.6 x 43.6 x 457.2 mm	
Packing Dimensions (W x H x D)	605 x 168 x 700 mm	
Certificated	CE/FCC	
Ordering Information		
KVM-1701COMBO-S	1U Rackmount 17" TFT LCD ,with 1 port KVM switch (Short Depth)	
KCVU-018 (optional)	USB, 2 in 1 KVM Cable , 1.8 meter length	
KCVU-030 (optional)	USB, 2 in 1 KVM Cable , 3.0 meter length	
KCVU-050 (optional)	USB, 2 in 1 KVM Cable , 5.0 meter length	
KCVP-018 (optional)	PS/2, 3 in 1 KVM Cable , 1.8 meter length	
KCVP-030 (optional)	PS/2, 3 in 1 KVM Cable , 3.0 meter length	
KCVP-050 (optional)	PS/2, 3 in 1 KVM Cable , 5.0 meter length	

Structure Diagram

Unit:mm

