

**Model: RMM-17W**  
 6U, 19" Rack mount 17.3" Full HD  
 LCD Monitor

**Model: RMM-17WT**  
 6U, 19" Rack mount 17.3" Full HD  
 LCD Monitor, with Touch screen



## Main Feature

- 17.3" Wide Screen Rack Mount LCD
- Full 1080p HD resolution (1920 x 1080)
- Install into 6U of rack space
- VGA, HDMI, Audio and BNC Inputs
- Option upgrade: Touch Screen and 3G-SDI input / output (loopback)
- Built-in audio speakers

Specification	
Product Model	RMM-17W   RMM-17WT
LCD Panel	Display Type : 17.3" Full HD LED Panel LCD Resolution : 1920 x 1080 Luminance : 300 cd/m2 View Angel : 140° (H), 120° (V)
Signal Input	VGA + HDMI + Audio + BNC
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Touch Screen ( optional )	Internal USB or RS-232 interface controller Type: Analog resistive type : 25VDC ≥ 20MΩ Light transmission: 80% or more Power consumption:<5V @1mA Surface hardness : 3H Operating force : ≤100g Life expectancy : 35 Million Operation system : Window 7 / 10/ CE, DOS , Linux
Signal Connectivity ( optional )	HD-SDI, 3G-SDI Input & Output (loopback)
DC Power Input ( optional )	Wide range DC 12V-24V input
Power Supply	DC12V@ 5A /60W ,external ac adapter
Construction	Heavy duty steel

Speaker	2x2 W Stereo internal speaker
Construction	Heavy duty steel
Environment	Operating temperature: 32 °F-113 °F (0 °C to 45 °C) Storage temperature: -4 °F-140 °F (-20 °C to 60 °C) Storage humidity: 10% to 95%@ 40 °C , on-condensing Vibration: 10 - 150Hz, 0.15mm 10 cycles 1G Shock: 30G peak acceleration (11 msec. duration)
Safety	CE/FCC/Rohs
Dimension W x H x D ( mm )	482 x 266 x 44mm
Weight	NET weight: 7KG      Gross weight: 9KG
<b>Ordering Information</b>	
RMM-17W	6U, 19" Rack mount 17.3" Full HD LCD monitor
RMM-17WT	6U, 19" Rack mount 17.3" Full HD LCD monitor, with Touch Screen
Optional: DC	Support DC input (12-24VDC)
Optional: SDI	Support HD-SDI, 3G-SDI Input & Output (loopback)

## Structure Diagram

