

Model: RMM-7X2-SDI
 3U, Dual 7" TFT LCD Rack Mount Monitor with SDI Input and Output



Main Feature

- 3U, 19" Rack Mount Two 7" TFT LCD Monitor
- Full 1080p HD resolution (1920 x 1200)
- Inputs: HDMI, 3G-SDI, LAN and Tally
- Output: HDMI, 3G-SDI
- HDMI supports 4K @ 60 Hz (2160p), 3G-SDI supports 1080p and lower
- Monitor and Control via LAN (IP address)
- Front-access OSD Controls

Specification	
Product Model	RMM-7X2-SDI
LCD Panel	Display Type : 7" Full HD LED Panel LCD Resolution : 1920 x 1200 Luminance : 400 nit Contrast: 2,000:1 View Angel : 160° (H), 160° (V)
Signal Input	HDMI x2 + 3G-SDI x2 + LAN + Tally
Signal Output	HDMI x2 + 3G-SDI x2 + Audio (Ear Plug)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Power Supply	DC12V@ 2A /24W, External AC adapter (12-24VDC Wide range input)
Construction	Heavy duty steel
Environment	Operating temperature: 32 °F~113 °F (0 °C to 45 °C) Storage temperature: -4 °F~140 °F (-20 °C to 60 °C) Storage humidity: 10% to 95%@ 40°C , on-condensing Vibration: 10 ~ 150Hz, 0.15mm 10 cycles 1G Shock: 30G peak acceleration (11 msec. duration)

Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	Dimensions: 480x132x29mm Packing Dimension: 600x190x 120mm
Weight	NET weight: 2.5KG Gross weight: 4KG
Ordering Information	
RMM-7X2-SDI	3U, Dual 7" TFT LCD Rack Mount Monitor with SDI Input and Output

Structure Diagram Unit :mm

