


Model: SSPM-19T
19" All Around IP66 Stainless Steel Touch Monitor



USB, HDMI & Power adapter and Cables included - 2 meters length each

Main Feature

- LED Panel – Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- Rugged Fanless Stainless Steel Cooling design
- Anti-scratch touch surface
- All around IP66 with waterproof connectors
- Industrial 5 wire Resistive touch screen, optional for PCT Touch
- 1 x HDMI, 2 x USB 2.0, 1 x Power-In
- 12 to 24VDC wide range input

Application:

Factory Automation, Food Processing Factory, Medical Equipment, Marine / Offshore Industrial, Kiosk

Specification	
Product Model	SSPM-19T
Display	Display Type : 19" SXGA <u>LED Panel</u> LCD Resolution : 1280 x 1024 Luminance : 250 cd/m2 View Angel : 170°(H), 160°(V)
I/O port	1 x HDMI; 1 x USB 2.0; 1 x 12-24VDC input
Touch Screen	Internal USB or RS-232 <u>industrial grade 5 wire Resistive Touch controller</u> Resolution: 4096 x 4096 Light transmission: 80% or more Surface hardness : 3H Operating force : ≤100g Life expectancy : 35 Million Operation system : Windows XP / 7 / 8.1 / 10 / CE, DOS , Linux
Power Supply	AC 100-240V wide range external AC adapter 12V/5A
Construction	All Around Stainless Steel

Environment	Operating temperature: -10°C to 60°C Relative humidity: 10% to 95%non-condensing Vibration: 17 to 500HZ 1G PTP; Shock: 1G /peak(11m sec)
Compliance	CE; FCC; ROHS
Dimension W x H x D (mm)	440 x 365 x 58 mm

Ordering Information

SSPM-19T	19'' All Around IP66 Stainless Steel Touch Monitor, with 100~240VAC to DC 12V 60W power adapter
----------	---

Structure Diagram

