

Model: STM-22
22" CCTV Security Monitor



Main Feature

- 22" WSXGA TFT LED Panel support 1680 × 1050 pixels
- Heavy duty steel chassis
- Rugged construction design
- Input signal : VGA + HDMI + 3 x BNC + Audio
- Build in 2 x 2 Watts stereo speaker
- OSD control keys to optimize the display, with Infrared Remote Controller
- AC 100-240V wide range AC power input
- Meet standard VESA hole (100 x 100 mm), support desktop stand/wall mount /swing arm mounting

| Specification | |
|---------------|--|
| Model | STM-22 |
| LCD Panel | Display Type: 22" WSXGA TFT LED Panel Resolution: 1680 x 1050 Max. color : 16.7M Luminance : 300 nit View Angel : 178°(H), 178°(V) Pixel Pitch : 0.282 x 0.282 mm Contrast Ratio : 1000 : 1 Response Time : 8 ms Power Consumption : 30W LED MTBF : 50,000hrs |
| Video System | PAL, NTSC 640 x 480p @ 60Hz 720 x 480p @60Hz 720 x 576p @ 50Hz 1,280 x 720p @ 50/60Hz 1,920 x 1,080i @ 50/60Hz |

| | |
|----------------------------|---|
| | 1,920 x 1,080p @ 50/60Hz |
| Filter Type | 3D Combo filter |
| Signal Input | VGA + HDMI + 2 x BNC + YPbPr (BNC) + 2 x Audio |
| Signal Output | BNC loop-out (for video recording) |
| Speaker | Built-in 2 x stereo speakers (2 watt) |
| OSD | Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall |
| Power Supply | Input: 100~240VAC, 50/60Hz |
| Power Consumption | Maximum: 40 watt |
| Construction | Heavy duty steel chassis |
| Environment | Operating temperature: 0 °C to 50 °C humidity: 10% to 95%, non-condensing |
| Dimension W x H x D (mm) | 500 x 327 x 67 |
| Net Weight | 8.5 KG |
| Ordering Information | |
| STM-22 | 22" CCTV Security Monitor |

Structure Diagram (unit: mm)

